

www.lindy.com

• DESCRIPTION:

The 70907 is 2 port Serial PCMCIA card which equipped with two RS-232.V24 Standard Serial-Interface, The serial port include 32 Byte FIFO

• Check your packing listing:

70907 Card Software Driver Hardware Guide 44PIN CONNECTOR TO 2S CABLE

• Hardware Specification

Serial Port:

UART Chipset: SUN1889, Hardware FIFO is 16Byte FIFO, Compatible chips: with 16C550 and 16C450. IEEE standard: RS-232 Interface Driver Chipset: HIN211.

• Hardware installation guide:

- Turn off the power of your computer
- > Plug-in the CBS2000 MIO Series Adapter to PCI bus of your computer
- Add-on the peripheral (Printer, Modem, Scanner... etc.) that you need to this Adapter
- > Turn on the power of your computer
- After The Screen, your Card install correct, you can install WINDOWS 2000 or XP, Please see INSTALL GUIDE

♦ TECHNICAL SPECIFICATION:

Compatibility:	-CARD BUSI 32Bit for 2K/XP
Operating system:	-WIN 2000,XP
Chips:	-1 x SUN1889
Connections:	-44 PIN TO 2 x 9 Pin D-SUB male
	connector serial
PCB:	- 2 Layer / 120 x 47 mm



(6

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operations.